*Slycma  Descriptions	<b>☎</b> : + 33 (0)4.78.86.81.00 <b>₤</b> : + 33 (0)4.78.86.81.08 ☑: slycma@slycma.com
Company:	••••••••••••••••••••••••••••••••••••••
Lift n°:	
Technical contact :	I Dolwory time required
□ ORDER	☐ QUOTATION
4 PANELS CENTRAL OPENING	Gaia 4V OC
CAR DOOR	EN 81-20 Gaia 47 OC CO 1200 to 2200
_	According drawing 2794700
04 00	OII.
☐ Automatic landing door unlocking ☐ Gaia 4V OC	CH:
Fixing height under fastening brackets : mm  Maxi 250 mm	
Other heigt > : (*) - Contact us for feasibil  Fixing kit on car roof (*)  2 C-Shaped section + screws and bolts  standard SLYCMA (Car door CO + 150 mm)  according to car width :  Vandal-resistant options (*)	ity
Category 2 with anti-gripping and panel's boxing on the whole height (Cowling Vandal-resistant unlocking device	of the lock contact included)
Blocking between floors	
□ Without (Non EN 81-20)	☐ Car door mechanical locking device between floors (*): EN 81-20 - Article 5.2.5.3.1
Stainless steel finishing and glazing (*)	
□ 304L Polished 220 brushed stainless steel cladding □ Glazir □ 304L D42 leather texture st. steel cladding - vandal-re □ 304L linen stainless steel cladding	ng ssistant option not available on glazed execution
Sills	
☐ Standard aluminium sill ☐ Non reinforced 304 L brush ☐ Iron sill (*) ☐ 304 L Reinforced stainless :  Toe guards (*)	ed stainless steel sill with removing dust slots (*) steel sill (*)
□ Large size toe guard (785mm) □ DELTACAP retractable toe g □ Galvanized iron □ William (pit from 500 to □ 304L stainless steel □ Jack 2 (pit from 660 to □ Sans fourniture de la tôle garde pieds □ Galvanized iron  Options (*)	660 mm)
☐ Infrared cells curtain with fixing kit	
◆ Literature ☐ French ☐ English ☐ German	□ltalian
Miscellaneous	
	98 -
	of the contract of the contrac