Company:			≅ : + 33 (0)4.78.86.81.00 √ : + 33 (0)4.78.86.81.08 ⋈ : slycma@slycma.com † : www.slycma.com
Lift n° :			Delivery time requested
	□ ORDER	□ QUOTATIO	Ν
4 PANELS CENTR	RAL OPENING		Rhea 4PCO
GLAZED CAR DO	DOR	EN 81 - 20	CO 600 to 1100
	←		
	_		According to drawing 2788600
☐ Automatic landing door unlocking ☐ Rhea 4PC0	Qty : CO : _	CH:	
\square Swinging door - Hung side seen from landi	☐ Swir	☐ right right right right right of opening of the car door miles that the direction of opening of the car door miles that the direction of opening of the car door miles.	oller height : mm ust be opposite to the hanging side of the swing door
Fixing height under fastening brackets : Other height > :(*) - (mm (mini 35 mm - maxi 3		ist be opposite to the hanging side of the swing door
Fixing kit on car roof (*) 2 C-Shaped section + screws and bolt standard SLYCMA (Car door C0 + 150) according to car width: Additionnal fixing stiffening adjustable Blocking between floors			
Mechanical car door locking device (VPC)	☐ EN 81-20 blocker (*)	☐ Without (Non EN 81-20)	
EN 81-20 - Article 5.2.5.3.1 (included in the sta	ndard production model)		
Stainless steel finishes (*) 304 Brushed massive stainless steel RAL powder coating	Nb of doors :	☐ 304 leathter texture massive stainless steel ☐ 304 linen massive stainless steel	® Nb of doors :
☐ Glazing of the panels ☐ Panoramic (standard model) : Panels ☐ Panels' edge and sill anodizat ☐ Full Glass (*) Sills	s' edge and sill : natural anodised alun tion (*) - colour :	ninium (Anodization according to Slycma referential)	
Standard aluminium sill Toe guards (*)	☐ Non reinforced 304 brushed	stainless steel sill (*)	
□ Large size toe guard (785mm) □ Galvanised iron □ 304 L stainless steel □ Without toe guard	☐ DELTACAP retractable toe gu☐ William (pit from 500 to☐ Jack 2 (pit from 660 to☐ Galvanised iron	660 mm)	☐ Adaptation kit ☐ Contact kit
Options (*)			
	e botton of pit (EN 81-20) (*) ∃English □ German	□ltalian	
Miscellaneous			
			September 2018
			S S S