



GAIA 2014/33/UE
EN 81-20/50

LANDING GLASS DOORS
NOT FIRE-RESISTANT



GAIA

2 and 4 panels landing door
Lateral and central opening
Non fire-resistant glazed door execution

Robust and easy to use are the main assets of this range.

Perfectly integrable in all the highly demanded environments such as office buildings, hotels, hospitals, shopping centers ... it can also be adapted to allow a complete or partial renovation.



GAIA landing door dimensions
Lateral and central opening
2 and 4 panels (in mm)

	MINI	MAXI
Clear opening (CO)	600 mm	2200 mm
Clear height (CH)	1900 mm	2500 mm
Standard header height	200 mm	
Full facade	Bunch post width : PL/2 + 50 (2P) ou PL/2 + 75 (4P) Slam post width : 110 mm	
Small facade	Uprights width : 110 mm	


Pictures for illustration purpose only - Realization SLYCMA 2017

NOT FIRE-RESISTANT

Ideal for **retrofitting** as well
as **new lift designs**

- Compliant with the EN 81 -20/50 standard
- Safety contacts available in accordance with the EN 81-21 standard
- Standard header 200 mm height


Standard




Primer




220 brushed stainless steel (*)




Leather texture stainless steel (*)



Square st. steel (*)



Linen st. steel (*)



5WL st. steel (*)



RAL painting (*)

Glass finishings



Antelios (*)



Bright (*)



Opal (*)

*Optional

SLYCMA associated with :
JET-S



SLYCMA Head office
Parc d'activité du Dôme
4 route du Dôme
69630 Chaponost
FRANCE
Tél. : +33 (0)4 78 86 81 00
Fax : +33 (0)4 78 86 81 08

SLYCMA Paris
34 route de Longjumeau
91380 Chilly-Mazarin
FRANCE
Tél. : +33 (0)1 69 79 32 10
Fax : +33 (0)1 69 79 32 15

www.slycma.com